

LED HIGHMAST / HIGHBAY LIGHTS

**RESELLERS OF OUR PRODUCTS ARE
AVAILABLE NATION WIDE.**

FOR RESELLER QUERIES AND WHOLESALE PRICELISTS / DISCOUNTS
PLEASE CONTACT OUR HEAD OFFICE.



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

37 WATT

PRODUCT CODES
37LB220CCR
PRODUCT DESCRIPTION
37W CCR LED Mid Bay Light in an anodized extruded aluminium housing with prismatic diffused or clear UHI UV resistant cover. The LED light is a locally developed OEM design to replace conventional HID mid bay lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. L-flange, U-Bracket or Chain Kit mounting options. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays
Surge and Lightning Protection & Replaceable Fuse
<ul style="list-style-type: none"> ● 5 YEAR GUARANTEE ● LOCALLY MANUFACTURED ● SABS TESTING IN PROGRESS



SPECIFICATION SUMMARY	
Rated Power:	37W (110VAC / 220VAC)
Light output:	3535lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP20 – IP65 (Specify)
Rated Lifetime:	> 80 000 HRS
Beam Angle:	140°diffused
Weight:	1 Kg
Dimensions:	330mm x 103mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

50 WATT

PRODUCT CODES

50D220CCR (Diffused)

50L220CCR (Lensed)

PRODUCT DESCRIPTION

50W CCR LED Mid Bay Light in an anodized extruded aluminium housing with prismatic diffused or clear UHI UV resistant cover. The LED light is a locally developed OEM design to replace conventional HID mid bay lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. L-flange, U-Bracket or Chain Kit mounting options. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays.

Surge and Lightning Protection & Replaceable Fuse

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**



SPECIFICATION SUMMARY

Rated Power:	50W (110VAC / 220VAC)
Light output:	4778lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP20 – IP65 (Specify)
Rated Lifetime:	> 80 000 HRS
Beam Angle:	140°diffused
Weight:	1,4 Kg
Dimensions:	480mm x 103mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

100 WATT

PRODUCT CODES
100D220CCR (Diffused)
100L220CCR (Lensed)
PRODUCT DESCRIPTION
100W CCR LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 100 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays.
U-bracket or chain kit mounting options Surge and Lightning Protection & Replaceable Fuse
<ul style="list-style-type: none"> ● 5 YEAR GUARANTEE ● LOCALLY MANUFACTURED ● SABS TESTING IN PROGRESS

Lensed Diffused



Chain kit



Wide Angle



Linear



U-bracket



SPECIFICATION SUMMARY	
Rated Power:	100W (110VAC / 220VAC)
Light output:	9556lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	140°diffused
Weight:	4 Kg
Dimensions:	330mm x 315mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

150 WATT

PRODUCT CODES

150D220CCR (Diffused)

150HM220-D

150L220CCR (Lensed)

150HB220V (Diffused)

PRODUCT DESCRIPTION

150W CCR LED Light consisting of an array of anodized aluminium extrusions with prismatic diffused polycarbonate UV resistant cover. The 150 W LED light is a locally developed OEM design to be used as high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays.

U-bracket or chain kit mounting options
Suitable to be used as High Bay Light also
Surge and Lightning Protection & Replaceable Fuse

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**

Lensed Diffused



Chain kit



Wide Angle



U-bracket



SPECIFICATION SUMMARY

Rated Power:	150W (110VAC / 220VAC)
Light output:	9556lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	140° wide beam
Weight:	6 Kg
Dimensions:	480mm x 315mm x 55mm 150HB220V (Diffused) : 330mm x 420mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

200 WATT

PRODUCT CODES
200Highmast-D (Diffused)
200HB2220D-CK (ChainKit)
200L220CCR (Lensed)
200HB220-5CK
200DR220-L (Dragline)
PRODUCT DESCRIPTION
<p>200W CCR LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 200 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. Perfect substitute for 400W HID conventional lights. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays.</p> <p>U-bracket or chain kit mounting options Surge and Lightning Protection & Replaceable Fuse</p> <ul style="list-style-type: none"> ● 5 YEAR GUARANTEE ● LOCALLY MANUFACTURED ● SABS TESTING IN PROGRESS



Lensed Diffused



Chain kit



Wide Angle

U-bracket

SPECIFICATION SUMMARY	
Rated Power:	200W (110VAC / 220VAC)
Light output:	14400lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	Diffused: 140° wide angle Lensed: 30° or 60°
Weight:	7,5 Kg
Dimensions:	480mm x 420mm x 55mm 200HB220-5CK: 330mm x 520mm x 55mm 200DR220-L (Dragline) 440mm x 485mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

250 WATT

PRODUCT CODES

- 250Highmast-D (Diffused)
- 250HB220D-CK (ChainKit)
- 250L220CCR (Lensed)
- 250DR220-L (Dragline)

PRODUCT DESCRIPTION

250W CCR LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 250 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. Suitable as substitute for 1000W HID Lights. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays. U-bracket or chain kit mounting options.

Surge and Lightning Protection & Replaceable Fuse

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**

Lensed

Diffused

Chain kit



Wide Angle

U-bracket



SPECIFICATION SUMMARY

Rated Power:	250W (110VAC / 220VAC)
Light output:	23890lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	Diffused: 140° wide angle Lensed: 30° or 60°
Weight:	9 Kg
Dimensions:	480mm x 525mm x 55mm 250DR220-L (Dragline): 575mm x 485mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

300 WATT

PRODUCT CODES

- 300Highmast-D (Diffused)
- 300HB220D-CK (ChainKit)
- 300L220CCR (Lensed)
- 300DR220-L (Dragline)

PRODUCT DESCRIPTION

300W CCR LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 300 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. Suitable as substitute for 1000W HID Lights. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays. High Mast Light is supplied with a U-bracket. High Bay Light supplied with chain kit.

Surge and Lightning Protection & Replaceable Fuse

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**

Lensed


Diffused

Chain kit



Wide Angle

U-bracket



SPECIFICATION SUMMARY

Rated Power:	300W (110VAC / 220VAC)
Light output:	28800lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	Diffused: 140° wide angle Lensed: 30° or 60°
Weight:	12 Kg
Dimensions:	480mm x 630mm x 55mm 300DR220-L (Dragline) 615mm x 480mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

350 WATT

PRODUCT CODES

350L220CCR

PRODUCT DESCRIPTION

350W LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 350 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. Suitable as substitute for 1000W HID Lights. Osramor Helvardrivers used on the luminaire. There is 100% output the moment the light is switched on, no warm-up or strike delays.

U-bracket or chain kit mounting options.
Surge and Lightning Protection & Replaceable Fuse

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**

Lensed



Chain kit



U-bracket



Diffused



SPECIFICATION SUMMARY

Rated Power:	350W (110VAC / 220VAC)
Light output:	37940lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	Diffused: 140° wide angle Lensed: 30° or 60°
Weight:	15 Kg
Dimensions:	480mm x 735mm x 55mm



DRIVERLESS HIGHBAY/ HIGHMAST LIGHT

400 WATT

PRODUCT CODES

400L220CCR

PRODUCT DESCRIPTION

400W CCR LED Light consisting of an array of anodized aluminium extrusions with ultra high impact UV resistant cover. The 400 W LED light is a locally developed OEM design to be used as area flood lights, high bay lights or high mast lights awarding the user with up to 65% energy cost savings and extended lifetime benefits. Suitable as substitute for 2000W HID Lights. New CCR driverless technology eliminating the need for third party drivers. There is 100% output the moment the light is switched on, no warm-up or strike delays. U-bracket or chain kit mounting options.

- **5 YEAR GUARANTEE**
- **LOCALLY MANUFACTURED**
- **SABS TESTING IN PROGRESS**



SPECIFICATION SUMMARY

Rated Power:	400W (110VAC / 220VAC)
Light output:	38400lm
Colour:	Warm White or Neutral White or Cool White
LED Technology:	Seoul LED
IP Rating:	IP65
Rated Lifetime:	> 80 000 HRS
Beam Angle:	Diffused: 140° wide angle Lensed: 30° or 60°
Weight:	14 Kg
Dimensions:	480mm x 840mm x 55mm

Chain kit

Lensed

Linear

U-bracket

